


THE FOLLOWING THERMAL CHARTS ARE TO BE USED TO DETERMINE OVERALL U VALUE OF THE PRODUCT BY KNOWING U VALUE CENTRE OF GLASS AND SELECTED SPACER OR DETERMINE CENTRE OF GLASS U VALUE AND SPACER BY KNOWING THE PRODUCT REQUIREMENTS FOR U VALUE.

- Curves represent tested simulation results based on double glazing options using the lowest (curve a) and highest (curve b) performing spacers. Spacer conductance values are based on NFRC 100-2010 section 5.9.5.1.
- Simulation methodology followed NFRC 100-2010
- Simulated curtain wall is 78 3/4" (2000mm) x 78 3/4" (2000mm) between mullion centres with one vertical central mullion as per NFRC 100-2010 table 4.3.
- The charts should be used as a budget or design guide for fenestration product u-factor and rating purposes.

A = Double glazed with Generic Group1  
 -Spacer containing aluminum  
 B = Double glazed with Generic Group4  
 -Spacer containing all non metallic materials

CHART BASED ON 1" (25.4 mm)  
 DOUBLE GLAZED SEALED UNIT



ENVIRONMENTAL CONDITIONS: NFRC 100-2001		
Inside Air Temperature	Outside Air Temperature	Outside Wind Speed
21° C	-18° C	5.5 m/s


Pour la version en français, veuillez voir la page : 1.7.2.5

THE FOLLOWING THERMAL CHARTS ARE TO BE USED TO DETERMINE OVERALL U VALUE OF THE PRODUCT BY KNOWING U VALUE CENTRE OF GLASS AND SELECTED SPACER OR DETERMINE CENTRE OF GLASS U VALUE AND SPACER BY KNOWING THE PRODUCT REQUIREMENTS FOR U VALUE.

- Curves represent tested simulation results based on triple glazing options using the lowest (curve a) and highest (curve b) performing spacers. Spacer conductance values are based on NFRC 100-2010 section 5.9.5.1.
- Simulation methodology followed NFRC 100-2010
- Simulated curtain wall is 78 3/4" (2000mm) x 78 3/4" (2000mm) between mullion centres with one vertical central mullion as per NFRC100-2010 table 4.3.
- The charts should be used as a budget or design guide for fenestration product u-factor and rating purposes.

A = Triple glazed with Generic Group1  
 -Spacer containing aluminum  
 B = Triple glazed with Generic Group4  
 -Spacer containing all non metallic materials

CHART BASED ON 1 3/4" (44.5 mm)  
 TRIPLE GLAZED SEALED UNIT



ENVIRONMENTAL CONDITIONS: NFRC 100-2001		
Inside Air Temperature	Outside Air Temperature	Outside Wind Speed
21° C	-18° C	5.5 m/s

Pour la version en français, veuillez voir la page : 1.7.2.6