



The Songhees Wellness Centre
Victoria, BC



UniVent 1350

Multi-point locking for 60-inch or larger project-out casements



Catalogue Pages



Specifications



CAD Details

www.alumicor.com

UniVent 1350



Multi-point locking for 60-inch or larger project-out casements

Features & Benefits

- Multi-point locking for 60" or larger project-out casements
- Can be integrated in all Alumicor curtain wall and window systems
- Open out and open in window options
- Polyamide thermal break permits two-color interior/exterior finishes
- 3 5/16" (84.1mm) Sight Line – Open in
- 2 17/32" (64.7mm) Sight Line – Open out
- 2 11/16" (68.3mm) System Depth – Dual IGU
- 3 7/16" (87.3mm) System Depth – Triple IGU
- Variety of operating hardware options
- Factory-fabricated at Alumicor facilities only



Alumicor UniVent 1350 Product Specifications

Application: For use in curtainwall and fixed window systems.

Description: Multi-point locking for 60-inch or larger project-out casements.

Face Width:	System Depth:	Glass:	Air:	Water:	Structural:	U-Factor**
80.9mm (3 3/16")	Dual Glazed: 68.3mm (2 11/16") Triple Glazed: 87.3mm (3 7/16")	Dual Glazed: 25.4mm (1") Triple Glazed: 44.5mm (1 3/4")	BHPI: 0.53 L/s.m.2 (1.12 cfm/ft2) @300Pa (6psf) SHPI: 0.53 L/s.m.2 (0.02 cfm/ft2) @300Pa (6psf) SHPO: 0.04 L/s.m.2 (0.008 cfm/ft2) @75Pa (1.5psf) THPO: 0.03 L/s.m.2 (0.005 cfm/ft2) @75Pa (1.5psf)	BHPI: 730Pa (15psf) SHPI: 730Pa (15psf) SHPO: 730Pa (15psf) THPO: 730Pa (15psf)	Design: BHPI: 3360Pa (70psf) SHPI: 3360Pa (70psf) SHPO: 5040Pa (105psf) THPO: 5040Pa (105psf) Overload: BHPI: 5040Pa (105psf) SHPI: 5040Pa (105psf) SHPO: 5760Pa (120psf) THPO: 5040Pa (105psf)	See U-Factor Table Online

** Refer to the U-Factor table at: www.alumicor.com/products/projected-windows/univent-1350/ for other glass makeups and configurations.