

***ADDITIONAL GLAZING DEPTHS IN THE RANGE OF 25-45mm MAY BE ACCOMMODATED USING GASKET COMBINATIONS. PLEASE CONTACT ALUMICOR FOR DESIGN ASSISTANCE.**

TW2200 CAPPED GLAZING INFILL OPTIONS

1	2681403	1/4" SPACER GASKET SILICONE, 60 DUROMETER	5	2644103	1/8" THERMAL BARRIER, FLEXIBLE PVC, 75 DUROMETER	11	2681903	17mm THERMAL BARRIER, RIGID PVC - DUAL DUROMETER	17	2250403	DBL GLA POCKET FILLER RIGID PVC
2	2249903	1/8" PRESSURE PLATE GASKET EPDM, 60 DUROMETER	6	2680703	1/4" THERMAL BARRIER, FLEXIBLE PVC, 75 DUROMETER	12	JC6001	19.5mm THERMAL BARRIER, RIGID PVC - DUAL DUROMETER	18	TW2280401	TPL GLA POCKET FILLER RIGID PVC
3	2554203	1/4" PRESSURE PLATE GASKET EPDM, 60 DUROMETER	7	2244101	9/32" THERMAL BARRIER, FLEXIBLE PVC, 75 DUROMETER	13	2681803	27mm THERMAL BARRIER, RIGID PVC - DUAL DUROMETER	19	2554803	DBL GLA POCKET FILLER RIGID PVC
4	PTB33	3/8" PRESSURE PLATE GASKET EPDM, 60 DUROMETER	8	2645103	3/8" THERMAL BARRIER, FLEXIBLE PVC, 75 DUROMETER	14	25132XX	GLAZING ADAPTOR ALUM. 6063 T6	20	TW2287103	SGL GLA SETTING BLOCK SILICONE, 80 DUROMETER
			9	JC11301	11mm THERMAL BARRIER, RIGID PVC - DUAL DUROMETER	15	25131XX	GLAZING ADAPTOR ALUM. 6063 T6	21	TW2287203	DBL GLA SETTING BLOCK SILICONE, 80 DUROMETER
			10	2380101	1/2" THERMAL BARRIER, RIGID PVC - DUAL DUROMETER	16	TW22853XX	GLAZING ADAPTOR ALUM. 6063 T6	22	TW2287303	TPL GLA SETTING BLOCK SILICONE, 80 DUROMETER



LAST REVISED: 10/17/25